



**KiilTO
PRO**

COLOUR CHART

CORE TILE GROUT

TILE GROUT

FLOOR TILE GROUT

EPOXY TILE GROUT

SANITARY SILICONE

SILICONE E

KIILTO PRO TILE GROUT

A water-repellent tile grout for tiles and clinker on walls and floors.

- joint width 1–6 mm
- for exterior and interior areas
- coverage 0,5–1,5 kg/m² depending on joint dimensions
- water- and dirt-repellent



KIILTO PRO SANITARY SILICONE



An anti-mould, odourless and neutral silicone for movement joints and sealing. Suitable for interior and exterior use.

	10	traffic white		41	stone
	11	linen		42	steel
	28	sand		43	pearl
	29	light beige		44	iron
	30	beige		46	silver
	31	toffee		48	antracite
	33	cocoa		50	graphite black
	36	terracotta		90	arctic
	38	ground brown		94	smoke
	39	marble white			
	40	concrete			
			(Only available in Saniteettisilikoni)		
				00	transparent

KIILTO PRO SILICONE E SANITARY SILICONE

An anti-mould, acetic acid based silicone for sealing movement joints of ceramic tiles, wall to floor junctions and joints between different materials as well as penetrations in wet areas. Also for exterior areas.

	000	transparent
	100	pure white
	139	marble white











KIILTO PRO CORE TILE GROUT

A special tile grout for floors and walls. Does not contain components that form efflorescence. Easy and fast to make a uniform joint with an even colour.

- suitable for grouting ceramic tiles and stones in residential and public spaces. For interior and exterior areas.
- good coverage, 0,3–1,5 kg/m² depending on the size of the joint and tile
- joint width 2–12 mm, 8 colours
- for professional use










	410	traffic white		443	pearl
	439	marble white		444	iron
	440	concrete		448	antracite
	441	stone		450	graphite black

KIILTO PRO FLOOR TILE GROUT

A fast-setting tile grout for clinker tiles and stone.

- joint width 2–12 mm
- easy-to-apply, can be washed off soon after grouting
- for interior and exterior areas
- water- and dirt-repellent









	238	ground brown		244	iron
	240	concrete		248	antracite
	241	stone		250	graphite black
	243	pearl			

KIILTO PRO EPOXY TILE GROUT

A two-component, epoxy resin based tile grout for ceramic tiles on challenging substrates in interior and exterior areas. Gives a waterproof joint with chemical resistance. Suitable also for fixing ceramic tiles.

- joint width 1–10 mm
- excellent resistance against mechanical wear and chemicals
- waterproof
- for professional use



	310	traffic white		340	silk grey
	329	light beige		344	quartz grey
	339	marble white		350	graphite black



CUSTOMER SERVICE

We will help you in the selection of the right products, and in questions regarding right working conditions and methods.

Weekdays 8.00 am – 4.00 pm

Customer service: +358 (0)207 710 100
customerservice@kiilto.com

Please note that the printed colour card may vary from the actual colour due to the printing technology used.

www.kiilto.fi